



Way of Life!

**JIMNY**

Smart in city, tough in nature.



# JIMNY

## ■ EQUIPMENT

	JIMNY	JIMNY
	4WD	4WD
	JL-SX	JL-DX
<b>COMFORT</b>		
Hydraulic power steering	x	●
Manual air conditioning	x	●
Heater	●	●
Antenna	●	●
Speaker x2	●	●
<b>INSTRUMENT PANEL</b>		
LED speedometer With fuel warning indicator	●	●
Tachometer	●	●
Instrument panel lighting colour Red	●	●
Light-off reminder	●	●
Key reminder	●	●
Steering wheel 3-spoke (Urethane)	●	●
Dashboard compartment Front passenger's side	●	●
<b>INTERIOR</b>		
Cabin light Front (3-position)	●	●
Sun visors	●	●
With vanity mirror, ticket holder	●	●
Day & night rear view mirror	●	●
Cup holders Front (center console) x 2	●	●
Rear (quarter trim) x 2	●	●
Floor carpet material Fabric	●	●
Front seats Sliding and reclining	●	●
Detachable head restraints	●	●
Walk-in mechanism (passenger's side)	●	●
Rearsetas Reclining	●	●
Split folding seatbacks	●	●
Detachable head restraints x 2	●	●
Single folding	●	●
Armrests Front door x 2	●	●
Assist grips Front passenger's side	●	●
Rear x 2	●	●
Door trims Moulded	●	●
Quarter trims Moulded, with pocket & cup holder	●	●
Luggage room under box	●	●
Remote fuel lid opener	●	●
<b>EXTERIOR</b>		
Halogen headlamps	●	●
Green tinted glass windows	●	●
Front window wipers 2-speed & intermittent & washer	●	●
Rear window wiper 1-speed & intermittent & washer	●	●
Rear window demister	●	●
Tyres 205/70R15 (15" aluminum)	●	●
<b>SAFETY &amp; SECURITY</b>		
Front seatbelts 3-point ELR x 2 with height-adjustable seatbelt anchors	●	●
Rear seatbelts 3-point ELR x 2	●	●
Side impact door beams Front doors	●	●
Immobilizer	●	●

PAK SUZUKI MOTOR CO. LTD. reserves the right to change without notice, prices, colours, materials and models.

## ■ SPECIFICATIONS

		JIMNY
		4WD
<b>DIMENSIONS</b>		
Overall length	mm	3,645
Overall width	mm	1,600
Overall height	mm	1,670
Wheelbase	mm	2,250
Tread	Front mm	1,355
	Rear mm	1,365
Ground clearance	mm	190
Manimum turning radius	m	4.9
Seating capacity	persons	4
Luggage capacity	Max. Volume (Manufacturer data) litre	816
	Rear seat back folder (VDA method) litre	324
	Rear seat back raised (VDA method) litre	113
<b>ENGINE</b>		
Type		M13A
Cylinder		4
Number of valves		16
Piston displacement	cc	1,328
Bore x stroke	mm	78.0 x 69.5
Compression ratio		9.5
Maximum output	kW/rpm	60/5,500
Maximum torque	Nm/rpm	110/4,500
Fuel distribution		MPI
<b>TRANSMISSION</b>		
		5(MT)
Gear ratio	1st	4.425
	2nd	2.304
	3rd	1.674
	4th	1.190
	5th	1.000
	Reverse	5.151
Final gear ratio		3.416
Transfer gear ratio	High	1.320
	Low	2.643
<b>CHASSIS</b>		
Steering		Recirculating ball
Brakes	Front	Disc
	Rear	Drum, leading & trailing
Suspension	Front	3-link rigid with coil spring
	Rear	3-link rigid with coil spring
Tyres	Standard	205/70R15
<b>WEIGHTS</b>		
		5(MT)
Curb weight (min.)	kg	1,060
Gross vehicle weight	kg	1,420

● Available  
x Not Available

 PAK SUZUKI MOTOR CO. LTD.

**Marketing Division Karachi:**  
DSU-13, Pak Steel Industrial Estate,  
Bin Qasim, Karachi.  
Call Centre: 111-SUZUKI (111-789-854)  
Fax: 34723521-3  
E-mail: marketing@paksuzuki.com.pk  
Website: www.paksuzuki.com.pk

**Lahore Area Office:**  
7-A, Canal Bank Road,  
Aziz Avenue, Gulberg-5,  
Lahore.  
Tel: 35775456-7  
Fax: 35775467

**Rawalpindi Area Office:**  
3rd Floor Malhi Plaza,  
Opp. Ministry of Defence  
Production Building, Murree  
Road, Rawalpindi Cantt.  
Tel: 5587518, 5518073,  
5790539  
Fax: 5587538

**Multan Area Office:**  
1812, Kharewal Road,  
Opp. Ali Raza CNG Station,  
Multan.  
Tel: 4516765, 4781127  
Fax: 4581128

